PRINT-BAN 150 FR

Product-description

Pile material	**100% PES**
Bonding	**The product is mechanically bonded by needling and thermal bonded by calandering.**
Colour	**White**

Analysis

PARAMETER	METHOD	VALUE	SPECIFICATIONS		
pile weight	ISO 9073-1	**150 g/m²**	135	- 165	g/m²
pile thickness (1)(4) - @2kPa	ISO 9073-2	**0,75 mm**	0,65	- 0,95	mm
tensile strength MD (2)(4)	ISO 9073-3	**400 N/5cm**	300	- 500	N/5cm
tensile strength CD (3)(4)	ISO 9073-3	**200 N/5cm**	150	- 250	N/5cm
elongation MD (2)(4)	ISO 9073-3	**19 %**	Max.	25	%
elongation CD (3)(4)	ISO 9073-3	**55 %**	Max.	80	%

(1) measured before packaging & transport (2) MD = machine direction (3) CD = cross direction (4)Unprinted

Customer information

Standard width (*)	**160cm - 200cm - 320cm - 400cm**
Standard lenght (*)	**100lm**
Core	**Carton**
Inner diameter tube (*)	**76mm / 3 inch**
Packaging (*)	**The roles are properly wrapped up in PE foil.** **The tube may stick out maximum 1 cm at both sides.** **Completely straight roles within +/- 5mm.**

(*) exceptional widths possible : moq or surcharge, with surcharge total produced volume should be accepted, no leftovers.

Product information

Application	***Inkt Printability*** Transfer Sublimation	Direct Sublimation	Screen Printing	Latex	UV	Eco Solvent	Solvent
Banner ■	■	■	■	***Evaluation***	■	■	■
Billboard ■	■	■	■	***Evaluation***	■	■	■
Back-lit							
Blockout							
Carpets							
Floor Mats							

MATEN®
www.mat-en.com

Aderente ad AIB

Made in Italy

CSI CERT ISO 9001
Sistema di gestione qualità accreditato