PRINT-BAN 300

Product-description

Pile material	**100% PES**
Bonding	**The product is mechanically bonded by needling and thermal bonded by calandering.**
Colour	**White**

Analysis

PARAMETER	METHOD	VALUE	SPECIFICATIONS	
pile weight	ISO 9073-1	**300 gr/m²**	270 - 330	gr/m²
pile thickness (1) - @2kPa	ISO 9073-2	**2,00 mm**	1,80 - 2,20	mm
tensile strength MD (2)	ISO 10319	**575 N/5cm**	475 - 675	N/5cm
tensile strength CD (3)	ISO 10319	**725 N/5cm**	600 - 850	N/5cm
elongation MD (2)	ISO 10319	**60 %**	15 - 105	%
elongation CD (3)	ISO 9073-3	**65 %**	40 - 90	%

Customer information

Standard width (*)	**200cm - 320cm - 400cm**
Standard lenght (*)	**25lm - 50lm**
Core	**Carton**
Inner diameter tube (*)	**76mm / 3 inch.**
Packaging (*)	**The roles are properly wrapped up in PE foil.** **The tube may stick out maximum 1 cm at both sides.** **Completely straight roles within +/- 5mm.**

(*) exceptional widths possible : moq or surcharge, with surcharge total produced volume should be accepted, no leftovers.

Product information

Application	***Inkt Printability***						
	Transfer Sublimation	Direct Sublimation	Screen Printing	Latex	UV	Eco Solvent	Solvent
Banner ■	■	■	■	***Evaluation***	■	■	■
Billboard ■	■	■	■	***Evaluation***	■	■	■
Back-lit							
Blockout							
Carpets ■	■	■	■	***Evaluation***	■	■	■
Floor Mats							

MATEN®
www.mat-en.com

Aderente ad AIB

Made in Italy

CSI CERT ISO 9001
Sistema di gestione qualità accreditato