

Entrance Mats PLASTIK 17 MISTO SPAZZOLA



SUGGESTED LOCATION


INDOOR ✓

COVERED
OUTDOOR ✓

OUTDOOR

STRENGTHS

- Ideal plastic structure for anti-theft
- Combined cleaning of fine dirt and drying action



Profile color range:

Black

Lead gray

- Technical data refer to the proposed alternation (1 needle-punched Aran and 1 brush). Are available on request other combinations.

Structure in robust PVC shock-proof and scratch-proof tubular profiles joined by thermoplastic high-strength channels perforated or closed. Space between the slats 5mm. Lining of rich technical needle punched alomdy appearance and monofilament tufts of nylon combined in the favourite relation. Thickness 17mm. c.a.


Overall thickness	17 mm
Weight	10,5 kg/m ²
Daily crossings	between 1000 and 2000
Distance between profiles	Standard 5 mm
Ligation	Draining standard (optional closed)
Profile's height	12 mm
Middle section profile	1,5 mm

Profile's material	Shockproof and scratch-proof PVC
Profile's MAX lenght	300 cm - 200 cm for outdoor
MAX lenght walkway	300 cm (also evaluable extraordinary lenghts)
Covering	Needle-punched ARAN 100% PP UV 1500 gr/m ² Section PA monofilament tufts of nylon 0,3 mm punched on thermoplastic support
Certifications	<ul style="list-style-type: none"> • Certificate of quality ISO 9001-2015

N.B. Mat.en's technical mats are a system of modular and rollable mats, trailerable and heelguard realized on shape and design on project. Are provided compensation profiles to reach the exact dimensions requested where necessary. Are counted 5mm air on measures communicated to allow the laying, the removal and the cleaning of the mats.

Entrance Mats PLASTIK 17 MISTO SPAZZOLA

Color range



Brush color



ACCESSORIES

Containing frame in: aluminium, steel and brass

Anodized aluminium finishing-lists

Anodized aluminium antistumbling trailerable ramp

Stripes of needle punched for replacement

Special silicone for bonding stripes of needle punched

Connectors for entrance mats

Stainless steel containment tanks (optional draining)

Acoustic foam

SERVICES

Survey with measures tracking

Installation

Shaping

Sanitation of the product

Maintenance, cleaning and repairs

Coating replacement

Technical consultancy

Graphic draft realization for customized mats

Sampling

CUSTOMIZATIONS

BART (stainless steel bar with laser engraving logo)

RAL profiles painting

CLEANING AND MAINTENANCE

To keep the carpets long-lived and working, we recommend to always check that the housing is levelled and in good condition and to ensure a thorough cleaning on a weekly basis.

- Aspire the top of the mat, roll it up and remove the dirt accumulated on the bottom with the help of a stiff bristle and vacuum cleaner (for draining channel).

- In case of stubborn dirt proceed after the ordinary cleaning with washing. Using a high pressure washer (at a minimum distance of 70cm), remove the accumulated dirt between the slats and on the coating. Allow the mat to dry completely, possibly vertically, before placing it back in its seat.

- To stain the textile coating, it's possible to clean the surface of the mat using warm water, laundry brush and the special soaking (can be purchased on www.mat-en.com).

In case the coating strips were irreversibly damaged (chewing gum, oil and cigarette burns) or in case of extreme wear you can contact the company for partial or total replacement.

It's possible to sanitize the mat with the appropriate specific products purchasable on www.mat-en.com.

CONSUMABLE

Mat.en offers a complete range of products designed for the maintenance, the cleaning and the sanitation of their products and the replacement of consumable accessories.

MATEN[®]
www.mat-en.com



Aderente ad AIB



Sistema di gestione qualità accreditato