

Doormats **ECOCLEAN 2.0**



SUGGESTED LOCATION

INDOOR ✓

COVERED
OUTDOOR

OUTDOOR

STRENGTHS

- Maximum drying
- 100% recycled and free PVC
- Available in measures

ECONYL®



Doormat carpet Ecoclean 2.0 Mat.en
100% PA recycled Econyle fiber.
PVC bottom
Thickness 8,5 mm
The product is subject to a dimensional tolerance of +/-1%

Overall thickness	8,5 mm
Weight	3,700 gr/m ²
Rolls size	20 x 2 ml c.a. (available welding)
Number of colors	1
Fleece	100% PA 1000 gr/m ²
Absorbency	5,0 L/m ²
Bottom	PVC
Certifications	<ul style="list-style-type: none"> • Certificate of quality ISO 9001-2015 • Certificate Cfi-s1

CLEANING AND MAINTENANCE

The Ecoclean 2.0 mat is self-laying and can be washed with water and a special degreaser (available at www.mat-en.com). We recommend daily cleaning with a vacuum cleaner or brush and avoiding beating the mat. Special care should be taken with mats featuring PVC ramps or welded seams. The use of pressure washers or steam cleaners is not recommended.

The mat can be sanitized using specific products available at www.mat-en.com

Color GAMME



EC 1

ACCESSORIES

Containment frame in: aluminium, steel and brass

Anodized aluminium wire cover

PVC trailerable anti-stumbling ramp

Foam mat 5 and 10mm

MATEN®
www.mat-en.com



Aderente ad AIB



Sistema di gestione qualità accreditato